MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174						
IDENTITY AND MANUFACTURER'S INFORMATION						
NFPA Rating: Health-1; Flammability-4; Reactivity-0; Special HMIS Rating: Health-1; Flammability-4; Reactivity-0; Personal Protection-B						
	DOT Hazard Classification: ORM-D					
	Identity (trade name as used on label):					
Address:						
Phone:	MSDS Number: A00183 Revision- 5					
EMERGENCY RESPONSE NUMBER:	Date Prepared: 04/23/07 Prepared By: ES/CH/IB					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	-	AS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
		74-30-0		1000	1000	ŭ
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: (concentrate only) = -43.7°F Specific Gravity (H2O=1): Concentrate Only = 0.54						
Vapor Pressure: PSIG @ 70°F (Aerosols): 70-80 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A						
Vapor Density (Air = 1): Concentrate only = greater than 1.5 Evaporation Rate (BuAc = 1): Faster						
Solubility in Water: Negible Water Reactive: No						
Appearance and Odor: Clear, odorless spray.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) 44-48 inches, flashback Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
to tip under partial actuator depression: Categorized: EXTREMELY FLAMMABLE N/E % LEL: 2.0 % UEL: 10.0						
FLASH POINT AND METHOD USED (non-aerosols): -156 °F						
SPECIAL FIRE FIGHTING PROCEDURES: Cool containers with water. Wear Self-contained breathing apparatus. carbon dioxide.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat, sparks, or any source of ignition.						
Hazardous Decomposition Products: CO, CO2.						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Product is an asphyxiant at very high concentrations. Excessive inhalation of vapors can be harmful and may cause headache,						
disorientation, rapid respiration, nausea, anesthetic effects and possible unconsciousness. Vapors are heavier than air and displace oxygen						
required for breathing. Abusive, excessive inhalation of vapors can result in asphyxia (death.)						
Eye Contact: May cause burns and frostbite. Skin Contact: May cause burns and frostbite.						
Ingestion: Unlikely route of exposure. Gas under normal (usual) circumstances.						
CHRONIC EFFECTS: Unknown.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush immediately with fresh water for at least 15 minutes while holding eyelids open. Remove contact lenses if worn. Seek						
medical attention immediately.						
Skin Contact: Treat burned or frostbitten skin by flushing or immersing affected areas in lukewarm water. If skin is not burned, keep warm and						
stimulate circulation with massage. Seek medical attention immediately.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Give oxygen.						
Ingestion: Unlikely route of exposure.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH to be used in a positive pressure mode.						
Protective Gloves: Rubber gloves recommended. Eye Protection: Safety glasses recommended. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Event Protection: Safety glasses recommended.						
Other Protective Clothing & Equipment: Self-contained respirator should be available for non-routine and emergency situations.						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Isolate hazard area and deny entry. Remove all ignition sources. Ventilate area to disperse vapors. If liquid gas has not ignited, disperse with water or by flooding.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Avoid contact with skin or						
eyes.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only